MICRO-OHMMETERS

MODEL 6240

Auto calculates resistance from $5\mu\Omega$ to 400Ω with resolutions down to $1\mu\Omega$



MODEL	6240						
Range	4000μΩ	$40 \text{m}\Omega$	400mΩ	4000mΩ	40Ω	400Ω	
Accuracy	±0.25% of Reading ±2cts						
Resolution	1μΩ	10μΩ	0.1mΩ	1mΩ	10mΩ	100mΩ	
Test Current	10A	1A	1A	100mA	10mA	10mA	
Max. Inductive Load	0 to 5 H						
Memory	Stores up to 99 test results						
Power Source	Rechargeable 6V, 8.5Ah NiMH battery pack (included)						



FEATURES

- Reliable low resistance measurements from $5\mu\Omega$ to 400Ω
- Four-terminal Kelvin resistance measurement eliminates test lead resistance
- 10A test current up to 4000μΩ
- ±0.25% basic accuracy
- 1μΩ resolution
- Direct reading, easy to operate
- Six selectable resistance ranges
- Reverse polarity switch
- Overload and input fuse protection
- Manufactured to international safety and environmental standards
- Automatic decimal point and zeroing
- Large terminals accept banana plugs and spaded lugs
- Rechargeable NiMH battery with internal charger (110/220V)
- Large multifunctional backlit display
- Includes power cord and isolated USB cable
- Includes FREE DataView software for data retrieval. real-time display, analysis and report generation



Extra large tool bag, set of two 10ft Kelvin clips (10A-Hippo), set of two 10ft Kelvin probes (1A - Spring Loaded), optical USB cable, US 115V power cord, two spare fuses (12.5A), NiMH rechargeable battery pack, and USB drive suppled with product user manual and DataView software.



ACCESSORIES

KELVIN CLIPS, SET OF TWO

Catalog #1017.84 (replacement) (10A - Hippo) 10ft Catalog #2118.70 (optional)





KELVIN CLIPS, SET OF TWO

Catalog #2118.79 (optional) (1-10A) 10ft

Catalog #2118.80 (optional)



KELVIN PROBES, SET OF TWO

Catalog #2118.77 (optional) (10A - spring loaded) 10ft Catalog #2118.78 (optional) (10A - spring loaded) 20ft



CATALOG NO.	DESCRIPTION	
2129.80	Micro-Ohmmeter Model 6240 (10A)	
Accessories/Replacement - available on website store from www.aemc.com		
1017.84	Kelvin Clips 10ft (10A - Hippo)	
2118.70	Kelvin Clips 20ft (10A - Hippo)	
2118.73	Kelvin Probes 10ft (1A, Spring Loaded)	
2118.74	Kelvin Probes 20ft (1A, Spring Loaded)	
2118.75	Kelvin Probes Pistol Grip (10A - Spring Loaded), 10ft	
2118.76	Kelvin Probes Pistol Grip (10A - Spring Loaded), 20ft	
2118.77	Kelvin Probes (10A - Spring Loaded), 10ft	
2118.78	Kelvin Probes (10A - Spring Loaded), 20ft	
2118.79	Kelvin Clips 10ft (1-10A) Replacement for Cat #2118.71	
2118.80	Kelvin Clips 20ft (1-10A) Replacement for Cat #2118.72	