

DET2/2 Auto Earth Tester



- High resolution - 1 mΩ - ideal for large earthing systems
- High accuracy for earth electrode and soil resistivity testing
- Test voltage 50 V max. for safety
- Rechargeable battery power with long battery life and rapid re-charge
- A robust, versatile instrument with IP54 protection
- Filter and high current features to enable valid earth testing in difficult situations

DESCRIPTION

The Megger® DET2/2 Auto Earth Tester is a robust compact instrument designed for measuring earth electrode resistance and soil resistivity. It uses the four terminal method of measurement which eliminates the resistance of the current circuit from the measurement. The circuit design ensures that the resistance of the potential circuit does not affect the measurement during practical testing.

The instrument is microprocessor controlled and provides a flexible, 'user-friendly' approach to earth testing by giving good error detection capabilities and full test information on a large easily readable alpha-numeric display. A simple key pad can be used to adjust the test frequency, the test current level and the filtering so that adverse conditions influencing the test may be overcome. The display indicates if:-

- the noise interference in the soil passing the test current is excessive.
- the current test spike resistance is too high.
- the potential test spike resistance is too high.
- the battery needs recharging

Because these factors are indicated directly the whole testing procedure is accomplished easily and more rapidly. A wide band of test current frequencies, with a resolution of 0,5 Hz, may be used to eliminate errors caused by

noise in the earth. The chosen test current frequency, test current level and the increased filtering option are stored in memory for use in subsequent tests.

The display can be set to show its information in the following languages:- English, French, German, Portuguese and Spanish.

The maximum output voltage is limited to 50 V for safety when performing a test and convenience when repositioning test spikes.

The instrument is auto-ranging relieving the operator of any concern as to which resistance range to use. The low service error and an IP 54 environmental specification enable accurate results to be obtained in 'unfriendly' testing conditions.

Power for the instrument is supplied from a rechargeable lead acid battery which gives 5 hours of life per charge, equivalent to six hundred individual tests lasting 30 seconds each.

The DET2/2 is built into a robust plastic case and has its four terminals, equipped for spade or 4 mm connectors, mounted on the front panel.

APPLICATION

The DET2/2 Earth Tester is a reliable instrument designed for larger or more complex earthing systems, including communications earthing systems and difficult testing environments. It may be used to test in accordance with BS 7430 (1991), the IEE Wiring Regulations and VDE

DET2/2 Auto Earth Tester

0413 part 7 (1982). The instrument is suitable for soil resistivity measurements, which are used to establish the optimum electrode design and site, as well as perform archeological and geological investigations.

Resistivity tests assist in the design of a correct earth system and avoid the cost of re-working electrode installations.

Earth testing kits, which include suitable test spikes and test leads, are available separately.

SPECIFICATIONS

Earth / ground resistance range

0.010 Ω to 19.99 k Ω (autoranging),
1 m Ω resolution.

Accuracy

(23 °C \pm 2 °C)
 \pm 0,5% of reading \pm 2 digits

Error

\pm 5% of reading \pm 2 digits \pm 10 m Ω
(meets VDE service error over 50 m Ω)

Compliance

BS 7430 (1991)
VDE 0413 Part 7 (1982)

Test frequency

105 to 160 Hz reversing d.c.
(50 Hz operation default to 128 Hz,
60 Hz operation default to 150 Hz)
Set in steps of 0,5 Hz

Test current range

50 mA max (selectable high and
low levels)

Maximum output voltage

< 50 V r.m.s.

Interference

Typically 40 V peak-to-peak
(50/60 Hz, sinusoidal nature)

Display

Alphanumeric L.C.D. (130 x 35 mm)
giving test information and a
large (20 mm) 3 1/2-digit reading)

Temperature co-efficient

< \pm 0.1% per °C over the
temperature range -10 to +40 °C
0.05% per °F from 14 to 104 °F

Operating temperature range and humidity

-10 to +40 °C (14 to 104 °F)

Storage temperature range and humidity

-20 to +60 °C (-4 to +140 °F)

IP rating

The instrument is waterproof to IP54

Flash test

3 kV ac

Voltage withstand

In the event of a system fault, the
instrument will withstand
240 V a.c. applied between any
two terminals.

Power supply

Internal
Rechargeable, sealed lead-acid
battery.
12 V (nominal), 2.6-Ah capacity.

Battery voltage over which basic
accuracy is maintained is 11.0 to
13.5 V.

Battery life

Approximately 5 hours continuous
use.

Battery charge time

6 hours max. (from completely
exhausted), charging current
automatically controlled to stop
over-charging.

Charging supply required
100 to 130 V or 200 to 260 V,
50/60 Hz.

Power consumption

9 W max. at 12 V

Safety

The instruments meet the
requirements of IEC61010-1.

EMC

In accordance with IEC 61326 -1.

Dimensions

245 mm x 344 mm x 158 mm

Weight

5 kg

Maximum current spike (loop) resistance

Range (RE)	Current (RC)	Current (RC)
0,010 to 0,499 Ω	5 k Ω	1 k Ω
0,500 to 1,999 Ω	5 k Ω	3 k Ω
2,000 to 19,99 Ω	10 k Ω	5 k Ω
(over 20 Ω RC > 20 k Ω)		

Maximum potential spike (loop) resistance

Range (RE)	Current (RP)	Current (RP)
0,010 to 0,499 Ω	11 k Ω	11 k Ω
0,500 to 1,999 Ω	21 k Ω	11 k Ω
2,000 to 19,99 Ω	21 k Ω	11 k Ω
(over 20 Ω RP > 20 k Ω)		

DET2/2

Auto Earth Tester

ORDERING INFORMATION

Description	Part number	Description	Part number
Auto Earth Tester	DET2-2		
Included Accessories		Optional Accessories	
Mains supply lead for battery charging		Comprising carrying case and pouch containing: Four galvanised steel spikes ('L' shape) 10 mm dia. (0.4 in. dia. approx) x 350 mm (14 in. approx) long	
Operating instruction book	6171-728	30 m (98,5 ft approx) of cable on a winder	
		50 m (164 ft approx) of cable on a winder	
		Two 3 m leads complete with connectors and clips	
		Hammer	
		Earth testing kit	6310-755
		Professional grounding testing kit 2 x 50 m, 2 x 30 m, 4 auger stakes, tape measure, in hard carry case	6320-245
		Terminal post to 4 mm skt adaptor set (x4)	1007-036

SALES OFFICE
Megger Limited
Archcliffe Road Dover
CT17 9EN England
T +44 (0) 1304 502101
E UKsales@megger.com

DET22_DS_en_V14
www.megger.com
ISO 9001
The word 'Megger' is a registered trademark

Megger[®]