



NEW!

Sonel S.A.
ul. Wokulskiego 11
58-100 Świdnica, PL
tel. +48 74 85 83 860
fax +48 74 85 83 809

export@sonel.pl
www.sonel.pl

INSULATION RESISTANCE METER

MIC-10k1 / MIC-5050

INSULATION
RESISTANCE
MEASUREMENT UP TO
40 TΩ
IN ACCORDANCE
WITH IEC 61557-2
MIC-10k1



CAT III
1000V
CAT IV
600V
EN
61557-2

 **Bluetooth®**
WIRELESS DATA TRANSMISSION

- Insulation resistance measurement:**
- up to 40 TΩ for MIC-10k,
 - up to 20 TΩ for MIC-5050,
 - measurement voltage any in the range of:
 • 50...5000 V for MIC-5050 (50...1000 V at 10 V and 1...5 kV at 25 V),
 • 50...10000 V for MIC-10k1 (50...1000 V at 25 V and 1...10 kV at 50V),
 - continuous indication of measured insulation resistance or leakage current,
 - automatic discharge of measured object capacitance voltage after the end of insulation resistance measurement,
 - acoustic signaling of 5 seconds intervals to facilitate capturing time characteristics,
 - adjustable measuring time to 99'59'',
 - metered T_1 , T_2 and T_3 test times for measuring one or two absorption coefficients from the range of 1...600 s,
 - polarization index (PI), absorption coefficients Ab1, Ab2 and dielectric absorption ratio (DAR) measurement,)
 - indication of actual test voltage during measurement,
 - 0.01nA ...1.2 mA, 3 mA and 6 mA test current accuracy of 2%,
 - insulation resistance measurement using two- or three-wire method,
 - Noise rejection-8mA
 - protection against measuring live objects,
 - automatic measurement of multiple core cables with the additional AutoISO-5000 adapter (for MIC-10k1 max. voltage 5 kV)
 - measurement of capacitance during the measurement of R_{iso} .
 - measurement of temperature (with additional probe - WASONT1),
 - step voltage insulation resistance measurement (SV),
 - Dielectric Discharge calculation (DD),
 - location of damage (burnout),
 - digital filters function for measurements in high noise environment
 - continuity measurement of protective connections and equipotential bonding in accordance with EN 61557-4 with current > 200 mA,
 - adjustable limits for measured resistance R_{iso} and R_{cont} ,
 - measurement of leakage current during insulation resistance testing,
 - DC and AC voltage measurement in the range of 0...750V,
 - drawing graphs on the display during measurement,
 - innovative memory with possibility of description of: measurement points, facilities, names of customers.
 - operating with mini Bluetooth keyboard (option),
 - graphic LCD 5,6" backlit,
 - keyboard backlit,
 - power supply from main power line or battery packs,
 - built-in fast charger,
 - the instruments meet the requirements of the EN 61557 standard.

MIC-10k1 / MIC-5050

Insulation resistance measurement

Measurement range acc. to IEC 61557-2 for MIC-5050 $U_n = 5000V$: 5,00MΩ...20,0TΩ,
for MIC-10k1 $U_n = 10000V$: 10,0MΩ...40,0TΩ

Range	Resolution	Accuracy
0...999 kΩ	1 kΩ	±(3% m.v. + 10 digits)
1,00...9,99 MΩ	0,01 MΩ	
10,0...99,9 MΩ	0,1 MΩ	
100...999 MΩ	1 MΩ	
1,00...9,99 GΩ	0,01 GΩ	
10,0...99,9 GΩ	0,1 GΩ	
100...999 GΩ	1 GΩ	
1,00...9,99 TΩ	0,01 TΩ	
10,0...20,0TΩ	0,1TΩ	±(12.5% m.v. + 10 digits)
10,0...40,0TΩ*		

* - only for MIC-10k1, $U_n = 10kV$

Values of measured resistance depending on measurement voltage

Voltage U_{iso}	Measurement range	AutoISO-5000 measurement range
50 V	200GΩ	20,0GΩ
100 V	400GΩ	40,0GΩ
250 V	1,00 TΩ	100 GΩ
500 V	2,00 TΩ	200 GΩ
1000 V	4,00 TΩ	400 GΩ
2500 V	10,00 TΩ	400 GΩ
5000 V	20,0TΩ	400 GΩ
10 000 V*	40,0TΩ*	-

* - only for MIC-10k1

Step voltage insulation resistance measurement

Voltage U_{iso}	MIC-5050	MIC-10k1
50...1000 V	10 V	25 V
1000...5000 V	25 V	50 V
5000...10000 V	-	50 V

Continuity measurement of protective connections and equipotential bonding with 200 mA current

Measurement range acc. to EN 61557-4: 0,12...999 Ω

Range	Resolution	Accuracy
0,00...19,99 Ω	0,01 Ω	±(2% m.v. + 3 digits)
20,0...199,9 Ω	0,1 Ω	
200...999Ω	1Ω	

• Voltage on open terminals: 4...24 V

• Output current at $R < 15 \Omega$: min. 200 mA (I_{sc} : 200...250 mA)

• Compensation of test lead resistance

• Current flowing in both directions, mean value of resistance is displayed

DC and AC voltage measurement

Range	Resolution	Accuracy
0,0...29,9 V	0,1 V	±(2% m.v. + 20 digits)
30,0...299,9 V	0,1 V	±(2% m.v. + 6 digits)
300...750 V	1 V	±(2% m.v. + 2 digits)

• Frequency range 45...65Hz

Measurement of capacitance

Display range	Resolution	Accuracy
0...999 nF	1 nF	±(5% m.v. + 5 digits)
1,00...49,99 μF	0,01 μF	

• capacity measurement result is displayed after the R_{so} measurement

• for measuring voltages under 100 V capacitance measurement accuracy not specified.

Measurement of temperature

Display range	Resolution	Accuracy
-40,0...99,9 °C	1 °C	±(3% m.v. + 8 digits)
-40,0...211,8 °F	1 °F	±(3% m.v. + 16 digits)

Standard accessories:

- test lead banana plug; 3 m; 10kV; red
- test lead banana plug; 3 m; 10 kV; blue
- test lead banana plug; 1,8 m; 10 kV; black; shielded
- USB cable
- "crocodile" clip 5,5kV; black
- "crocodile" clip 5,5kV; red
- "crocodile" clip 5,5kV; blue
- pin probe 10 kV with banana connector; red
- pin probe 10 kV with banana connector; black
- carrying case L4 for accessories
- power cord
- battery pack (built-in)
- "SONEL Reader" software
- calibration certificate

WAPRZ3X0REBB10K
WAPRZ3X0BUBB10K
WAPRZ3X0BLBEE10K
WAPRZUSB
WAKROBL32K07
WAKRORE32K07
WAKROBU32K07
WASONREOB10X0
WASONBLOGB10X0
WAFUTL4
WAPRZ1X8BLIEC

Electrical safety:

- type of insulation double, in acc. with EN 61010-1 and IEC 61557
- measurement category IV 600 V (III 1000 V) in acc. with EN 61010-1
- case protection rating in acc. with EN 60529 IP40 (IP67 - with lid closed)

Other technical specifications:

- power supply of the meter built-in battery pack approx. 7kg
- weight of the meter 390 x 310 x 180 mm
- dimensions graphic LCD 5,6"
- display USB or Bluetooth
- transmission of measurement results

The acronym "m.v." stands for a "measured reference value".